



C A P E L L A
SERIES 33/43
DIRECT VENT GAS FIREPLACE INSERT

Unit illustrated is an IDV43N Direct Vent Insert – Natural Gas, MQLOGF453 Driftwood Log Set, MQRSP11 Support Platform for Driftwood, I43CV5BL Clean View – Black, I43SF1BL Door Frame – Black, I43BT4432BL Back Trim Surround – Black, IDV36PRL Porcelain Reflective Liner.

TRIM OPTIONS

BLACK

PEWTER

VINTAGE COPPER VEIN

STYLING



ROCK COLLECTION



DECORATIVE STONE



FIVE PIECE DRIFTWOOD SET (IDV43 ONLY)



FIBRE SPLIT OAK LOG SET



DECORATIVE EMBER GLASS

BRICK LINERS



HERRINGBONE (IDV43 ONLY)



TRADITIONAL



FLUTED (IDV33 ONLY)

DESIGNER DOORS & FRAMES



DOOR FRAME



DESIGNER DOOR



INSERT Your Style Here

Transform your existing **wood burning** fireplace into an updated focal point with the Capella insert. Beautifully crafted, the Capella features the expansive Clean View and adapts easily to your style.

The unit illustrated is a IDV33N Direct Vent Fireplace Inset – Natural Gas LOGF35 Split Oak Log Set, IDV33PRL Porcelain Reflective Liner, I33CV3BL Clean View Kit – Black.



Unit illustrated is an IDV43N Direct Vent Inset – Natural Gas, I43CV1BL Clean View – Black, MQRSP8 Glass Support Platform, MQSTONE Decorative Stones, IDV36PRL Porcelain Reflective Liner.



Unit illustrated is an IDV43N Direct Vent Inset – Natural Gas, I43CV1BL Clean View – Black, MQRSP8 Glass Support Platform, MQG5A Decorative Ember Glass – Cobalt Blue, IDV36PRL Porcelain Reflective Liner.

Model	IDV33N	IDV33LP	IDV43N	IDV43LP
	IDV33NE / IDV33NE2	IDV33LPE / IDV33LPE2	IDV43NE / IDV43NE2	IDV43LPE / IDV43LPE2
Fuel	NATURAL	PROPANE	NATURAL	PROPANE
Input	31,000 BTU	28,500 BTU	34,250 BTU	30,000 BTU
Low	20,900 BTU	23,100 BTU	24,000 BTU	22,840 BTU
FE (P.4.1-02)	57.4%	57.9%	61 / 62%	61 / 62%
Flue Sizes	3/3"	3/3"	4/3"	4/3"

MINIMUM FIREPLACE OPENING

MODEL	Width	Height	Depth	MODEL	Width	Height	Depth
IDV33	26 1/4"	21 3/8"	14 3/8"	IDV43	30 3/4"	25 5/8"	14 3/4"

LOUVER KIT AND SURROUND SIZES

IDV33	Width	Height	IDV43	Width	Height
I33LK (Louver Kit)	34 1/2"	24 3/8"	I43LK (Louver Kit)	39"	28 3/4"
I33S3426 (Surround)	34 1/2"	26 1/2"	I43LKS1BL (Surround Universal)	39"	31 3/4"
I33S4028 (Surround)	40"	28 1/8"	I43LKS2BL (Surround Universal)	44"	32 3/8"
I33S4430 (Surround)	44"	30 5/8"	I43LKS3BL (Surround Universal)	47"	36"
I33USR4BL (Surround Universal)	45"	35"			

CLEAN VIEW AND SURROUND SIZES

Minimum Fireplace Opening: 26 3/8"W x 21 3/8"H x 14 3/8"D IDV33 INSERT				Minimum Fireplace Opening: 30 3/4"W x 25 5/8"H x 14 3/4"D IDV43 INSERT			
	Width	Height	Depth		Width	Height	Depth
I33CV (Clean View)**	33 3/8"	23"/24 5/16"	2 1/2"	I43CV1 (Clean View)**	37 1/2"	27 1/4"/28 3/4"	2 1/2"
I33CV3 (Clean View)**	33 5/8"	23 5/8"/24 5/16"	4 1/8"	I43CV3 (Clean View)**	37 3/4"	27 3/8"/28 3/4"	4 1/8"
I33SR2 (Surround)	39"	27"	5/8"	I43S4432 (Surround)	44"	32"	5/8"
I33SRP3 (Surround Picture Frame)	41"	31"	5/8"	I43US4736 (Surround Universal)	47"	36"	1/6"
I33USR4 (Surround Universal)	45"	35"	1/6"	I43SPF1 (Surround Picture Frame)	43 1/2"	33 3/8"	1/2"
I33CV5 (Clean View)	37 1/8"	25 1/4"	2 5/16"	I43CV5 (Clean View)	41 3/16"	29 1/16"	2 5/16"
I33BT1 (Back Trim Surround)*	39"	26"	1 1/4"	I43BT4230 (Back Trim Surround)*	42"	30"	1 1/4"
I33USR4 (Surround Universal)	45"	35"	1/6"	I43BT4432 (Back Trim Surround)*	44"	32"	1 1/4"
I33CVPF5 (Clean View Picture Frame)	37 1/8"	25 1/4"	2 5/16"	I43US4736 (Surround Universal)	47"	36"	1/6"
I33BTPF (Back Trim Surround)*	41"	31"	1 1/4"				

* Back Trim Surround required if the fireplace opening is smaller than 29 3/8"W x 22 3/8"H x 16 1/8"D.
Note: When Using I33CV5/I33CVPF5 Clean View a Door Frame or Designer Door Frame is Required.
**CV and CV3 have a tapered profile.

* Back Trim Surround required if the fireplace opening is smaller than 33 1/2"W x 26 5/8"H x 16 5/8".
Note: When Using I43CV5/I43CVPF5 Clean View a Door Frame or Designer Door Frame is Required.
**CV1 and CV3 have a tapered profile.

Minimum Fireplace Opening: 29 3/8"W x 22 3/8"H x 16 1/8"D IDV33 INSERT				Minimum Fireplace Opening: 33 1/2"W x 26 5/8"H x 16 5/8"D IDV43 INSERT			
	Width	Height	Depth		Width	Height	Depth
I33CV5 (Clean View)	37 1/8"	25 1/4"	2 5/16"	I43CV5 (Clean View)	41 3/16"	29 1/16"	2 1/4"
I33SR2 (Surround)	39"	27"	5/8"	I43S4432 (Surround)	44"	32"	5/8"
I33USR4 (Surround Universal)	45"	34"	1/6"	I43US4736 (Surround Universal)	47"	36"	1/6"
I33CVPF5 (Clean View Picture Frame)	37 1/8"	25 1/4"	2 1/4"				
I33SRP3 (Surround Picture Frame)	41"	31"	5/8"				

Note: When Using I43CV5 Clean View a Door Frame or Designer Door Frame is Required.

- The unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, MQRCK3 Contemporary Rock Collection – Multi-Coloured, MQRSP4 Rock Support Platform, I33CVPW Clean View Kit - Pewter, I33S1PW Surround – Clean View – Pewter, IDV33PRL Porcelain Reflective Liner.
- The unit illustrated is a IDV43N Direct Vent Insert – Natural Gas, LOGF36 Oak Log Set, I43LK Louver Kit, IDV36RLT Refractory Brick Liner – Traditional.

STANDARD FEATURES*

- > Dual Burner with glowing embers and decorative ash bed
- > Millivolt or IPI (intermittent pilot ignition) valve system allows operation during power failure with adjustable flame control
- > Heat activated blower with variable speed control
- > Heat radiating Ceramic Glass
- > On/Off Rocker switch
- > Proflame II Models include Remote Control – Features flame, fan, thermostat, smart thermostat, CPI/IPI cold climate control (IDV33NE2, IDV33LPE2, IDV43NE2, IDV43LPE2 Models only)



OPTIONAL FEATURES

- Clean View Kit – Black (I33CV/I43CV1 Pewter and Copper Vein available)
- Surrounds for Clean View – Black (I33SR2/I43S4432 Pewter and Copper Vein available)
- Surround Picture Frame for Clean View – Black
- Louver Kit – Grills (Black)
- Surrounds for Louver Kit – Black
- Wall Mount Thermostat – Standard On/Off or Programmable
- Remote Control (Millivolt or IPI PF1) – On/Off, Thermostat, Modulating Thermostat



- Contemporary Rock Collection* – Natural or Multi-Coloured (Rock Support Platform required)
- Decorative Stones or Ember Chunks – (Glass Support Platform required)
- Decorative Ember Glass* – Glacier Ice, White, Cobalt (Blue), Black or Bronze (Glass Support Platform required)
- Log Set – Fibre Split Oak and Driftwood
- Porcelain Reflective Liner
- Brick Refractory Liner – Traditional, Herringbone (IDV43 only) or Black Fluted (IDV33 only)
- Designer Door – Black with Safety Screen (Requires CV5)
- Designer Frame – Black with Safety Screen (Requires CV5)

* All gas fireplaces manufactured as of January 1, 2015 will include a Safety Screen Barrier.





 **marquis**
COLLECTION | by Kingsman

Kingsman Fireplaces, maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

The Units are Certified to: ANSI Z21.88-2014, CSA 2.33-2014, CGA 2.17-M91 (R2009) Vented Gas Fireplace Heater.

*Components may have to be ordered separately to create a complete unit. Discuss with your local Marquis Dealer for clarification.

